

Model Name	CityRide 20
Chassis Platform	LPO 1628 BS III Diesel; 45 seater
Engine	ISBe 285 EIII Cummins; Water cooled, Turbocharged & After cooled diesel engine; 6700 cc
Maximum Power	285 HP at 2500 RPM
Maximum Torque	970 at 1700 RPM
Gear Box	6+1 ZF 6S1000 BO Manual compatible to SAE 1 housing
Clutch Diameter	430 Dia 2000 sq cm
Suspension	Front: ZF independent air suspension; Rear: Wheels India 4 bag suspension
Retarder	Voith Hydro dynamic Retarder for Rear Engine-VR 120-4
Tire Size	16 R 22.5 Tube less Radial/ IMichelin tyre 295 / 80 R 22.5
Steering	Integrated ZF steering (Stg. GB part of ZF Axle Assy)
Brakes	Front: Disc Brakes (ZF) Rear: 220x697 S-Cam
Fuel Tank Capacity	400 litres
Wheelbase	6095 mm
Front Overhang	2550 mm
Rear Overhang	3350 mm
No of Seats	45,41,39,37 options
Max Width	2500 mm
Passenger Door	Pneumatic swing in
Overall Length	11995 mm
Overall Height In Laden Condition	1260 mm
Turning Circle Diameter	17890 mm
Maximum Speed	116 kmph
GVW	16200 kg
Electricals	Battery: 2x12 Volts, 180 Ah; Alternator Capacity: 180 Amps