

Descriptions	LPK 909 Ex BSIII		Advantages	
Engine	Tata 497 TCIC BSIII - Water-cooled Direct Injection Diese	I Engine with Inter-cooler		
Fuel Injection Pump	Electronic Rotary Type (VP37 - Mico)			
Power	92 Kw (125 Ps) @ 2400 rpm			
Torque	400 Nm @ 1300 - 1500 rpm			
Clutch Type	Single Plate Dry (310 mm)		LOW ON MAINTENANCE INCREASE	D EARNINGS AIR BRAKES
Gearbox	TATA GBS 40 Synchromesh - 5F + 1R			
Front Axle	Heavy Duty Forged I Beam, Reverse Elliot Type			
Rear Axle	Banjo - Single Reduction, Hypoid Gears, Fully Floating Axle Shafts			
Tyres	8.25 x 16		COMFORT ASSURED HIGH HO	RSEPOWER HEAVY DUTY
Steering Type	Power Steering (18.8:1)	AND	TORQUE AGGREGATES	
Front Suspension	Semi-elliptical Leaf with Double Acting Telescopic Type Shock Absorbers			
Rear Suspension	Semi-elliptical Leaf with Auxiliary Springs & Double Acting Telescopic Type Shock Absorbers			E Carton
Brakes	Full S-Cam Air Brake with Foot-operated Dual Treadle Valve acting on all wheels with Automatic Wear Adjusters		N AGE	
Parking Brakes	Graduated Valve-controlled Spring Brake Chamber Integral with Rear Brake Actuator			
Engine Exhaust Brake	Coupled with Service Brakes with Electro-magnetic Air Cylinder & Electrical Isolator Switch			
Min. Ground Clearance (mm)	217			
Gradeability	28%		UK NO	
Battery	12V - 100AH			
Fuel Tank Capacity (ltrs)	90			
FAW (kg)	3250			
RAW (kg)	6350		TATA MOTORS RECON	(ŐŘ)
GVW (kg)	9600		(Avail Recon Unit Exchange for Engine Long Block & Components)	TATA MOTORS Contified PRE-OWNED COMMERCIAL VEHICLES
	Dimensions		Write to us: reconsales@tatamotors.com	Write to us: tataok@tatamotors.com SMS: 5616161
	FULLY BUILT	CAB	Call us on: 1800-20	SAMP© ©RNA SEVA (Annual Maintenance Contract Facility) To avail Sampoorna Seva
Wheel Base (mm)	2775		Write to us: delight@tatamotors.com or Visit us at: www.tatadelight.com	at affordable price for your vehicle, Call us on: 1800-258-2589 (Toll-free) Write to us: amccustomer@tatamotors.com
Front Wheel Track (mm)	1687		CAUTION: Do not weld or drill on chassis	
Rear Wheel Track (mm)	1671		CAUTION: Do not weld or drill on chassis frame • Accessories shown in the picture or elsewhere do not constitute standard fitments. • The specifications are indicative. Due to continuous product improvements, these specifications are liable to change without notice.	
Turning Circle Radius (mt)	5.		For more information, please visit our website: www.tatamotors.com. You can also contact	
Loading Length (ft)	10.7	NA	our Sales Office: Tata Motors Limited, 20th Floor, Tower 2, One Indiabulls Centre, 841, Senapati Bapat Marg, Mumbai 400 013. Tel: 91 22 6658 6000; Fax: 91 22 6658 6010.	
Length x Width x Height (mm)	3260 x 2035 x 700	NA	Dealer stamp	
Loading Volume (cum)	5	NA	NA	
Tipping Angle	53 Degree			
Hydraulic Cylinder	Single RAM, Two Stage, Telescopic, Double Acting			
Warranty	3 years / 3 lakh km, whichever is earlier, on all aggregates			