

The comfortable way to
higher earnings

LPT
1109H Ex2
Sleeper Cab



| | |
|-------------------------------|---|
| Engine | 497 TCIC BSIII |
| Fuel Injection Pump | Electronic Rotatory Type (VP 37 - MICO) |
| Power | 125 PS @ 2400 rpm |
| Torque | 400 Nm @ 1300-1500 |
| Clutch Type | Single Plate Dry (330 mm) |
| Gear Box | GBS - 40 Synchronesh (5F+1R) |
| Front Axle | Heavy Duty Forged I Beam, Reverse Elliot Type |
| Rear Axle | Single Reduction, Hypoid Gears, Fully Floating Axle Shafts |
| Tyres | 8.25 x 20 -16 PR |
| Steering Type | Hydraulic Power-assisted |
| Front Suspension | Semi-elliptical Leaf Spring |
| Rear Suspension | Semi-elliptical Leaf Spring |
| Brakes | Dual Circuit Full Air S-cam Brake (360 mm) |
| Parking Brakes | Hand-operated |
| Engine Exhaust Brake | Air-operated coupled with Service Brake with Electro-magnetic Air Cylinder & Electrical Isolator Switch |
| Min. Ground Clearance (mm) | 225 |
| Gradeability | 18% |
| Max. Speed in Top Gear (kmph) | 80 |
| Battery | 12 V, 100 AH |



LPT
1109HEx2
Sleeper Cab

Technical Specifications

| | | | |
|---------------------------|--|------------------|------------|
| Fuel Tank Capacity (ltrs) | 160 | | |
| FAW (kg) | 4670 | | |
| RAW (kg) | 8320 | | |
| GVW (kg) | 12990 | | |
| DIMENSIONS | | | |
| | CLB | High Deck | CAB |
| Wheelbase (mm) | 4200/4830 | | |
| Turning Circle Radius (m) | 8.35/9.50 | | |
| Loading Length (ft) | 17.91/19.98 | 17.91/19.98 | NA |
| Length (mm) | 5460/6090 | 5460/6090 | NA |
| Width (mm) | 2157 | 2167 | NA |
| Height (mm) | 603 | 1800 | NA |
| Loading Area (sq. m) | 11.78/13.14 | 11.83/13.20 | NA |
| Warranty | 18 months/1.5 lakh km, whichever is earlier, on all aggregates | | |



Call us on: 1800-209-7979 (Toll-free)

TATA MOTORS

For more information, please visit our website: www.tatamotors.com. You can also contact our Sales Office: Tata Motors Limited, 20th Floor, Tower 2, One Indiabulls Centre, 841, Senapati Bapat Marg, Mumbai 400 013. Tel: 91 22 6658 6000; Fax: 91 22 6658 6010.

CAUTION: Accessories shown in the picture or elsewhere do not constitute standard fitment. The specifications are merely indicative. Due to continuous product improvements, these specifications are liable to change without notice.