

PRIMA

LX 4028.S SR

Perfect balance of

Economy & Turnaround Time





Engine
High performance 267 HP
CRDi engine by Cummins



Gearbox
Proven Tata G1150
9-speed gearbox




Rear Axle Heavy duty RA 110 axle ideal for high performance highway applications



Cabin
World class Prima LX cabin
with best-in-class driving comfort





LX 4028.S SR

erima

Dimensions (mm)

Overall Width

Overall Length

Front Overhang

Unladen Weight

Gearbox & Clutch

Turning Circle Diameter

Wheelbase

Weight (kg)

Max. GCW

Max. FAW

Max. RAW

Engine

Model Cummins ISBe 270 BSIII

Type Water-cooled Direct Injection Turbo-charged,

After-cooled Diesel Engine; 6 Inline

Other Details Bore / Stroke: 107 mm x 124 mm

Firing Order: 1-5-3-6-2-4

Air Filter: Dry type remote mounted
Oil Filter: Full flow spin on paper type
Fuel Filter: Pre and fine filtration with

water separator

Volume 6700 cc

Power 267 HP @ 2500 rpm

Torque 970 Nm @ 1200-1700 rpm

FIP HPCR

Model G1150 OD 9-speed

2585

5898

3460

1482

12900

6790

40200

6000

10200

Synchromesh on all forward speeds;

Constant mesh on reverse

Speed 8F + 1Cr + 1RGear Ratios Crawler - 9.37

> 1st - 6.654, 2nd - 4.897 3rd - 3.571, 4th - 2.69 5th - 1.863, 6th - 1.370

7th - 1.0, 8th - 0.75, Rev - 9.757

Single Disc, Dry Friction Type

Clutch Dia 430 mm Push Type Area - 1984 sq cm

Rear Drive Axle

Clutch Type

Type Tata RA 110 RR

Axle Ratio 5.86

Chassis & Suspension

Size 286 mm x 90 mm x 7 mm

Type Fully reinforced

Front Suspension Parabolic Leaf 90 mm width

Rear Suspension Semi-elliptical Multi Leaf Spring 90 mm width

Brake

Type Full Air S-Cam Dual Circuit with ABS

Cabin and Steering System

Type Fully Floating Sleeper Cabin Hydraulic Tilt Type

Steering Tilt & Telescopic Adjustable

Steering Wheel Diameter - 470 mm

Integral Hydraulic Power-assisted Ratio: 24.2

Instrument Cluster Digital
AC Optional

Tyres

Tyres 10R20-16PR/10x20 optional

Fuel Tank

Fuel Tank (Itrs) 400

Fuel Tank (ltrs)
Performance

Max. Geared Speed

in Top Gear (kmph) 100 kmph

Max. Gradeability

in Crawler Gear 17.92%

Telematics/GPS Tracking

Telematics unit as standard fitment

Service activation optional (Contact 1800 209 7979)







Enroll Today! Write to us: delight@tatamotors.com or Visit us at: www.tatadelight.com

Call us on: 1800-209-7979 (Toll-free)





(Annual Maintenance Contract Facility)

To avail Sampoorna Seva at affordable price for your vehicle, Write to us: 1800-258-2589 (Toll-free) Email: amccustomer@tatamotors.com

TATA MOTORS

For more information, please visit our website: www.tataprima.com. You can also contact our Sales Office: Tata Motors Limited, 20th Floor, Tower 2, One Indiabulls Centre, 841, Senapati Bapat Marg, Mumbai 400 013. Tel: 91 22 6658 6000; Fax: 91 22 6658 6010.

The illustrations and photographs may show accessories and items of optional equipment which are not part of standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrades without prior notice, in accordance with the Company's policy of continuous improvement.

