

THE PERFORMANCE THAT OUTPERFORMS.



SPECIFICATIONS - XENON DICOR

Model	4SPCR10
Туре	Water-cooled direct injection
	Common rail turbocharged
	Intercooled diesel engine
Capacity (cc)	2956 сс
Max Output (Hp) at RPM	85 Hp @ 3000 RPM
Max Torque (Nm) at RPM	250 Nm @ 1000-2000 RPM
STEERING	
Туре	Power Steering
SUSPENSION	
Front	Semi-elliptical leafspring
Rear	Two stage semi-elliptical
	leafspring
PERFORMANCE	leafspring
PERFORMANCE Maximum Speed	leafspring 120 Km/hr

FUEL TANK	
Capacity	60 Litres
GEARBOX	
No. of Gears	5 Forward, 1 Reverse
TYRES & WHEELS	
Туре	215 / 75 R16 Radial
DIMENSION	
Wheel Base (mm)	3150
Overall Length (mm)	5361
Load Body L x B (mm)	2565 x 1675
Gross Vehicle Weight (Kgs)	2950
Seating Capacity	1+1
WARRANTY	
3 Years/3 Lakh Kms [#]	



Powerful DICOR Engine



Rigid Front Suspension



Best-in-Class Mileage

Lowest-in-Class Maintenance

For more information, contact: Tata Motors Limited, Commercial Vehicles Business Unit, 20th Floor, Tower 2, One Indiabulls Centre, 841, Senapati Bapat Marg, Mumbai - 400 013. Tel: (022) 6658 6000 Toll-free: 1800 209 7979 Fax: (022) 6658 6010.

Website: www.xenon.tatamotors.com or SMS* <XENON PICKUP> to 5616161

The illustrations and photographs may show accessories and items of optional equipment that are not part of standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement.

